



PRV015S120V230

---

**Eaton 15HP 3PH 208V  
62CFM Energy Efficient  
Variable Speed Rotary  
Screw Swing Arm ::  
115CFM Dryer :: 120  
Gallon Horizontal Tank -  
Matte Black w/ Auto Drain  
& Hydraulic Hoses**

---





|                                    |                  |
|------------------------------------|------------------|
| <b>Weight</b>                      | 1562 lbs         |
| <b>Brands</b>                      | EATON COMPRESSOR |
| <b>HP</b>                          | 15               |
| <b>Tank Size</b>                   | 120              |
| <b>Voltage +/- 10%</b>             | 230              |
| <b>Phase</b>                       | 3                |
| <b>Drive Type</b>                  | Electric         |
| <b>Tank Drain</b>                  | Automatic        |
| <b>CFM</b>                         | 62               |
| <b>Silent Air</b>                  | N                |
| <b>Smart Air</b>                   | Y                |
| <b>Compressor Type</b>             | ROTARY           |
| <b>Motor Type</b>                  | ODP              |
| <b>Tank Orientation</b>            | Horizontal       |
| <b>Duty Cycle</b>                  | 1                |
| <b>Outlet Size</b>                 | 1"               |
| <b>Belt Count</b>                  | 2                |
| <b>Pump Stage</b>                  | 1                |
| <b>Pump Riser</b>                  | N                |
| <b>Belt Tensioner</b>              | N                |
| <b>Mag Starter</b>                 | N                |
| <b>Radiator</b>                    | N                |
| <b>Continuous Run</b>              | N                |
| <b>Peak Starting Amps</b>          | 237              |
| <b>Motor RPM</b>                   | 1750             |
| <b>FLA + 1.15 Service Factor</b>   | 57.5             |
| <b>Locked Rotor Amps</b>           | 237              |
| <b>Recommended Breaker</b>         | 50               |
| <b>Max PSI</b>                     | 167              |
| <b>Uncrated Weight</b>             | 880              |
| <b>Oil Capacity</b>                | 1.5              |
| <b>Oil U/M</b>                     | Gallons          |
| <b>Estimated Pump Life (Hours)</b> | 100000           |
| <b>Certifications</b>              | UL/CSE           |
| <b>Service Kit</b>                 | SKIT003WB        |